

A CSW Industrials Company

### PRODUCT DATA SHEET

## **DUST FREE® VERSALIGHT**

Germicidal UV Light

## **Description**

The Bio-Fighter® VersaLight is a UV-C light system designed for HVAC applications, ensuring powerful germicidal protection. Offers single or dual remote-mount lamp capabilities and features a multi-voltage power supply, adapting from 120V to 240V. The high-output lamps provide effective disinfection, and the unit's robust stainless steel construction makes it durable and moisture-resistant.



### **Characteristics | Features**

- Versatility: Single or dual remote-mount capability allows flexibility in unit location and application.
- Durability: Stainless steel construction protects against corrosion and accidental damage.
- Multiple Lamp Lengths.: 14", 16", and 20" lamp lengths. Single and dual lamp models.
- Moisture Resistant- Extra long 6-ft lamp cables with moisture boot seals lamp connections against moisture in high humidity environments.
- Easy Maintenance: User-friendly slide-clip lamp retention system makes lamp replacement easier.
- Convenience: Lighted On/Off switch and external fuse are conveniently located.

### **Packaging**

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case	
DF06154	UV Bio-Fighter Multivolt 2SVL16	1	7.95	0.64	
DF06153	UV Bio-Fighter 1SVL16 MV	1	7.60	0.64	
Replacement Filter					
DF06033	UV Light Bulb Replacement Standard 20"	1	0.90	0.05	
DF06032	UV Light Bulb Replacement 16"	1	0.50	0.04	
DF06157	Replacement Lamp single 14" HO	1	0.85	0.04	

# **DUST FREE® VERSALIGHT**

Germicidal UV Light

3.437"---

### **Specifications**

Model	Single Lamp:         Dual Lamp:           1SVL14 - DF06151         2S14 - DF061           1SVL16 - DF06153         2SV16 - DF06           1SVL20 - DF06155         2SV20 - DF06           1SVL00 - DF06208         2SV00 - DF06	-154 :156		3.437
Size and Weight	Unit: 13" L x 4.5" W x 2.625" H Remote Housing: 3.6" L x 3" W x 1.25" H Weight: Versalight 1S - 5.75 lbs. Versalight 2S - 6 lbs		IIC-HIGHTER  / AFSAL (GHT  Secondary Improved Light  1.8.	
Electrical	120V-240V, 50/60Hz, multi-voltage electronic ballast. Full load amps: 120V – 0.9 amps. 240V – 0.5 amps. 3 amp 250V fuse. 120V, 3-prong, 6 ft., detachable power cord		0 0	3.625* Remote Lamp Housing
UV-C Output (µw/cm2)	530 to 1,650 microwatts* depending on model *Tested at 50° F, 12", 500FPM air velocity			125
Lamp Life	9,000 hour			
Ozone	None with standard bulbs. Ozone generating bulbs available as an option			
Temperature Rating	45° to 150° F (Outside of duct)			
Warranty	3-yr limited. 1-yr lamp			

### Sizing

The single lamp Bio-Fighter® VersaLight is suitable for slab coil applications 3 tons or less, and 1200 CFM or less. Or where space permits only a single lamp. The dual lamp Bio-Fighter® VersaLight is suitable for slab coil, A-coil, and return air applications, where space permits dual lamps. For optimum results and maximum UV-C output, dual lamp units are recommended for A-coil and return air applications.

### Installation

The Bio-Fighter® VersaLight remote-mount UV-C lamp system can be mounted anywhere in the HVAC system or ductwork. The preferred installation location is near the cooling coil where mold infestation is most likely.



#### **Limited Warranty**



For more information on our product limited warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com